

DESCRIPTION

Design			Classic / Anticwood /Ship / Mineral
Thickness	ISO 24346	mm	3.00 ± 0.20 0.12' ± 0.0008"
Weight	ISO 23997	kg/m ² lb/sq.Yd	2.60 ± 0.250 4.8
Roll width		cm	200 (-0 +1) 6.56'
Roll length		lm	24 78.72'

PERFORMANCE

Dimensional stability	ISO 23999 ASTM D 1204	%	≤ 0.2
Abrasion resistance	TABER ISO 9352	mg oz	250 ± 50 0.008 ± 0.002
Static punch resistance	ISO 24343-1	mm Inch	≤ 0.35 ≤ 0.014"
Low temperature resistance	D 42 1235 A	°C °F	- 20 4
Sound damping characteristics	ISO 717/2	dB	ΔI = 14
Colour fastness	ISO 105 B02 ISO 4582/80 ASTM D 4459		≥ 6
Fire resistance	ISO 3795/76	mm/mn	0
	FMVSS 302		Conform
	NF PA 253 ASTM E648	W/cm ²	CRF > 0.50
	R118		Conform
Resistance to chemicals	ISO 26987	-	Unaffected by diluted acids and bases Unaffected by domestic products (excluding solvents for plasticized PVC)